OCHIAI **TEA GARDEN MANAGEMENT** MULTIPURPOSE OPERATION MACHINE



OMR-5

SPEC | F | CATION

MODEL		OMR-5	Е	MODEL	4 CYCLE DIESEL
SIZE	LENGTH	1,680 mm	N G I N E	DISPLACEMENT	1,330 cc
	WIDTH	2,120 mm (@GAUGE 1,800)		OUTPUT	20.0kW(27.2PS)/2800(rpm)
	HEIGHT	RUBBER 2,407mm IRON 2,426mm		FUEL CAPACITY	20 l
GAUGE		1,600 ~ 1,800mm	CRAWLER		RUBBER 230 × 72 × 47
CLIMBABLE ANGLE		15°			IRON 230 × 90 × 36
OPERATIONAL ANGLE		10°		RUNNING SPEED	0~4.7 km/h

ATTACHMENT

1	R-5D	DEEP CULTIVATOR
2	R-5T	COMPOST SPRAYER
3	R-5H	HUMMER ROTOR
4	R-5B	SPRAYER
5	R-5CI	FERTILIZER AND CULTIVATOR
6	R-5P	DUAL LEVEL PRUNER
7	R-5S	SUBSOILER
8	R-5R	FERTILIZER SPRAYER
9	R-5W	SIDE CUTTER



OCHIAI CUTLERY MANUFACTURING CO.,LTD.





OMR-5 ATTACHMENT

1. R-5D DEEP CULTIVATOR



Softented soil is ideal for root's growth.

More air in the soil, more vigor the Maximum Depth:

≪Work Efficiency≫10a/30min (※it might be changed depends on

2. R-5T COMPOST SPRAYER



2 rows simultaneous spraying conveyor mechanism enbles smooth application It is more easy to put compost by height 200mm lower than previous model.

Load capacity:0.9m

≪Work Efficiency≫10a/15~20min (%it might be changed depends on fields condition)



Crushing trees with hummer, and trimming with pruner. Pruning unit installed with chain

> ≪Work Efficiency≫10a/60min (%it might be changed depends on fields condition)

R-5B SPRAYER



× Picture rear boom specification fromt boom specification available Maximum pump suction: 56L/min

Horizontal elastic booms are free from tips getting caught

Tank capacity:500L 3 rows convering booms

 \ll Work Efficiency \gg 10a/12 \sim 15min (Xit might be changed depends on fields condition)



 $R-5C \Pi$ FERTILIZER AND CULTIVATOR

> Loading capacity Chemical;100KG/unit Compound:80KG/unit

Same time operation both fertilizing and cultivating One unit Two purpose

 \ll Work Efficiency \gg 10a/15 \sim 20min (Xit might be changed depends on fields condition)

※R−5C Cultivator only available

DUAL LEVEL PRUNER R-5P

Pruning capability 200-300mm with one operation(dual operation) Chain conveyor enables smooth discard

Using blades instead of hummer rotor prevents trunk cracking

> \ll Work Efficiency \gg 10a/120min (Xit might be changed depends on fields condition)

Xsingle operation model avaiable

7. R-5S SUBSOILER



Vibrating arms crushes hardened soil layers

Maximum Depth : 300mm

≪Work Efficiency≫10a/15min (**%**it might be changed depends on fields condition)

8. R-5R FERTILIZER SPRAYER



2 rows simultaneous application Adjustable splaying plate enables

Loading Capacity:80kg/unit

≪Work Efficiency≫10a/15~20min (%it might be changed depends on fields condition)



Secures the path way between tree rows 1 side, 2 sides models available Pruning attachment can be installed when single side side cutting

> ≪Work Efficiency≫10a/20min (※it might be changed depends on fields condition)