

乗用型OMT


OCHIAI

magnificent power, stability, various attachments enable to adopt to series of operations, efficient middle size combine machine

NEW

乗用型中刈複合機

OMT-6BT(S)型



Cultivator Attachment
OMT-D1



Subsoiler attachment

OMT-S2



※写真は鉄クロラタイプ

Characteristics

1. Installed screw conveyor drops 80% of cut branches between rows.
2. One man operated. Front-side free hummer breaks trees, mid-section blade arranges
3. Variety of attachments (back-side pruner, various depth cultivator, fertilizer sprayer) enable high efficiency
4. Attachment can be installed easily with exclusive cart
5. Fixed gauge, variable gauge available

Specification

Model		OMS-6BT		Climbable angle	15° (maximum)
Engine	Type	4cycle vertical water cooling straight 4 cylinder diesel		Crawler	Rubber 230xP72x58L
	Displacement	2197cc			Iron 230xP90x46L
	Rating	33.8KW(43PS)/2600rpm		measurement	Length 2260mm
	Fuel capacity	40ℓ			Width 2300mm
Speed		0-3.6km/h		Height	2580mm
Blade	Hummer	Free hummer type		Frame center height	960mm
		Width 1640mm	Height 480-950mm		
	pruner	Installed in mid-section R3000		Operator	1 man
Width 1700mm		Height 470-720mm			
Gauge		1600-1800mm		workload	10a/h(pruning)